



● POWER WIRING INTERFACE POINTS
 ○ CONTROL WIRING INTERFACE POINTS
 * ALL CONTROL WIRING IS DISCRETIONARY

REMOTE ALARM CONTACTS*
 2A @ 250 VAC

REMOTE ALARM CONTACT*
 0.6A @ 125VAC
 0.6A @ 110VAC
 2.0A @ 30VDC



PROPRIETARY AND CONFIDENTIAL - THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF UTILITY SYSTEMS TECHNOLOGIES, INC.
 ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF UTILITY SYSTEMS TECHNOLOGIES, INC. IS PROHIBITED

REV: 2 DATE: JANUARY 21, 2009
 REV: 1 DATE: AUGUST 15, 2008
 REV: 0 DATE: DECEMBER 03, 2007

Utility Systems Technologies, Inc. PO Box 110, Latham New York 12110		
TITLE: STD 1PH ISOLATION XFMR SURE-VOLT ELECTRICAL SCHEMATIC		
SIZE: A	DWG NO.: EVR-0000-000S-000	REV: 1
SCALE: NONE	SHEET: 1 OF 1	