



● POWER WIRING INTERFACE POINTS  
 ○ CONTROL WIRING INTERFACE POINTS  
 \* ALL CONTROL WIRING IS DISCRETIONARY

**REMOTE ALARM CONTACT\***  
 0.6A @ 125VAC  
 0.6A @ 110VAC  
 2.0A @ 30VDC



**Utility Systems Technologies, Inc.**  
 PO Box 110, Latham New York 12110

**TITLE:**  
 STD 3 PH ISOLATION XFMR SURE-VOLT ELECTRICAL SCHEMATIC

REV: 2 DATE: January 22, 2009  
 REV: 1 DATE: AUGUST 15, 2008  
 REV: 0 DATE: DECEMBER 03, 2007

<b>SIZE:</b>	<b>DWG NO.:</b>	<b>REV:</b>
<b>A</b>	<b>EVR-0000-000D-000</b>	<b>1</b>

PROPRIETARY AND CONFIDENTIAL - THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF UTILITY SYSTEMS TECHNOLOGIES, INC.  
 ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF UTILITY SYSTEMS TECHNOLOGIES, INC. IS PROHIBITED

<b>SCALE:</b>	<b>SHEET:</b>
NONE	1 OF 1